

1.8 Meter VSAT Antenna

- 1) Double shape ring-focus
- 2) Accurate in adjustment and fashionable design
- 3) Strong in anti-corrosion
- 4) We can provide Ku-Band and linear polarization
- 5) High gain and excellent sidelobe performance
- 6) Excellent in stability
- 7) Custom tailor product

| SPECIFICATIONS | 1.8 meter VSAT Antenna | |
|---------------------------------------|--|-------------|
| | Ku-RECEIVE | Ku-TRANSMIT |
| Frequency (GHz) | 10.95-12.75 | 13.75-14.5 |
| Typical Gain(dBi) | 44.98 | 46.29 |
| VSWR | 1.25:1 | |
| Beamwidth:-3dB | 0.926° | 0.796° |
| -15dB | 1.852° | 1.59° |
| Antenna Noise Temperature(° K) | 2Port Feed | |
| 10° Elevation | 43 | |
| 20° Elevation | 39 | |
| 40° Elevation | 35 | |
| Power Handling Capability | 1KW/Port | |
| Feed interface | WR-75 | |
| Cross Polarization Isolation(on axis) | ≥35dB | |
| Sidelobes | CCIR. 580-4 | |
| Feed Insertion Loss | 0.2dB | |
| Tx-Rx | ≥85dB | |
| Environmental | | |
| Relative humidity | 0% to 100% | |
| Seismic(Survival) | 0.3G s horizontal 0.15G s vertical | |
| Operational Winds | 45mi/h(72km/h) gusts to 60mi/h(97km/h) | |
| Survival Winds | 125mi/h(200km/h) | |
| Ambient Temperature | -45° to 60° | |
| Mechanical | | |
| Elevation Travel | 0° to 90° | |
| Surface Accuracy | 0.5mm(R. M. S) | |
| Antenna Optics | Ring-focus antenna | |
| Azimuth Travel | 360° | |